



1 On/off button 2 Battery mode indicator 3 Line mode indicator 4 USB Type-A 5V/2A Output 5 USB Type-C QC/PD Output 6 AC Input

Main Specifications

- For powering devices such as WiFis, Routers, Modems, VOIP, cameras and charging Tablets, Smartphones, Bluetooth headsets, Smartwatches, ecc
- 5.200 mAh Lithium-ion batteries
- Included 4 connectors: compatibility with most devices
- DC 12V 100cm output cable for connection to modem/router
- Overload and Short circuit protection
- Overvoltage protection
- Temperature control inside

Specifications

UPS Model	ERA PLUS DC - USB 5VDC 2A, USB-C OUTPUT 5V/9V/12V/15V/20V
Code	FGCERAPLDC253C
Nominal Power	25 W Max
Technology	Switching with Lithium-ion batteries
Cooling	Natural
Audible noise	< 40 dBA at 1 m
Input connections	2 PIN Italy plug AC input cable
Output connections	USB Type-C - USB Type-A
Dimensions (UPS) WxHxD	7,6x3,2x9,3cm
Dimensions (with packing) WxHxD	9,3x4,2x13,5cm
Weight	0,5 Kg
Included	AC Input cable -100cm length - USB Type-C to 5,5x2,5mm connector - 12V 3 connectors (3,5x1,35mm - 4,8x1,7mm - 5,5x2,1mm)
Input	
Nominal voltage	Single-phase 230Vac
Input voltage range	110-240Vac
Nominal frequency	50/60 Hz
Output	
USB Type-A port	5V/2A
USB Type-C port	5V/5A - 9V/2,77A - 12V/2,08A - 15V/1,66A - 20V/1,25A
Overload capability	< 130%
Transfer time	0 ms
Battery	
Type	ICR 18650 - 3.7Vdc - 2.600 mAh x2
Capacity	3.7Vdc - 5.200 mAh - 20Wh
Backup time (typical)	240 min
Environmental specification	
Working temperature	From 0 to 45 °C (recommended from 20 to 25 °C)
Humidity	< 95% without condensation
Maximum altitude	3000 m
IP protection	IP20
Certifications	CE

© 2024 Tecnoware Power Systems. The technical data may change without prior notice.

Easily replaceable batteries



Included

